

SPM Series Source Measuring Unit Technical Specifications

The instrument must be operated continuously for more than 30 minutes at the specified operating temperature to achieve the following specifications:

Power supply parameter

Specifications	SPM3051	SPM6053	SPM3103	SPM6103
Input Characteristics				
Supply Voltage	110Vac \pm 15% or 220Vac \pm 15%, please supply power according to the mark on the left of the power input socket on the rear panel of the instrument			
Input Frequency	45~65Hz	45~65Hz	45~65Hz	45~65Hz
Input Parameter 1 (110Vac\pm15%)				
Input Voltage Range	93~127Vac	93~127Vac	93~127Vac	93~127Vac
Full Load Input Current	\leq 2.8A	\leq 5.6A	\leq 5.6A	\leq 5.6A
No-Load Input Current	\leq 200mA	\leq 300mA	\leq 300mA	\leq 300mA
Input Fuse	250V,F5A	250V,F10A	250V,F10A	250V,F10A
Input Parameter 2 (220Vac\pm15%)				
Input Voltage Range	187~253Vac	187~253Vac	187~253Vac	187~253Vac
Full Load Input Current	\leq 1.4A	\leq 2.8A	\leq 2.8A	\leq 2.8A
No-Load Input Current	\leq 100mA	\leq 150mA	\leq 150mA	\leq 150mA
Input Fuse	250V,F3A	250V,F5A	250V,F5A	250V,F5A
Rated Output				
Rated Output	0~30V	0~60V	0~30V	0~60V
Voltage	0~5A	0~5A	0~10A	0~10A
Current	150W	300W	300W	300W
Efficiency (110Vac, rated load)	80%	80%	80%	80%
Efficiency (220Vac, rated load)	85%	85%	85%	85%
Regulation(CV)				

Specifications	SPM3051	SPM6053	SPM3103	SPM6103
Load	≤30mV	≤30mV	≤30mV	≤30mV
Line	≤20mV	≤20mV	≤20mV	≤20mV
Regulation(CC)				
Load	≤30mA	≤30mA	≤30mA	≤30mA
Line	≤20mA	≤20mA	≤20mA	≤20mA
Ripple & Noise (Noise bandwidth 20MHz, ripple bandwidth 1MHz, connect 10uF electrolytic capacitor in parallel with 0.1uF ceramic capacitor to the output terminal for testing)				
Voltage (Vp-p)	≤30mV	≤30mV	≤30mV	≤50mV
Voltage (rms)	≤3mV	≤3mV	≤3mV	≤5mV
Current (Ap-p)	≤30mA	≤30mA	≤30mA	≤30mA
Setting Resolution				
Voltage	10mV	10mV	10mV	10mV
Current	1mA	1mA	1mA	1mA
Readback Resolution				
Voltage	10mV	10mV	10mV	10mV
Current	1mA	1mA	1mA	1mA
Setting Accuracy				
Voltage	≤0.1%±20mV	≤0.1%±20mV	≤0.1%±20mV	≤0.1%±30mV
Current	≤0.1%±10mA	≤0.1%±10mA	≤0.1%±10mA	≤0.1%±10mA
Readback Accuracy				
Voltage	≤0.1%±20mV	≤0.1%±20mV	≤0.1%±20mV	≤0.1%±30mV
Current	≤0.1%±10mA	≤0.1%±10mA	≤0.1%±10mA	≤0.1%±10mA
Response time				
Transient recovery time (50%~100% rated load)	≤1ms			
Protective function				

Specifications	SPM3051	SPM6053	SPM3103	SPM6103
OVP	0~31V	0~61V	0~31V	0~61V
OCP	0~5.1A	0~5.1A	0~10.1A	0~10.1A
OTP	85°C	85°C	85°C	85°C
Temperature coefficient of output				
Voltage	100ppm/°C			
Current	200ppm/°C			
Temperature coefficient of readback value				
Voltage	100ppm/°C			
Current	200ppm/°C			

DMM parameters

Characteristics	Instruction	
Display	19999	
measurement	Voltage, current, resistance, capacitor, diode, on-off	
Input Impedance	≥ 10 MΩ	
Diodes Test	0~2V	
Function	Measurement Range	Function
DC Voltage	200.00mV	±(0.3%+10dig)
	2.0000V/20.000V/200.00V	±(0.3%+5dig)
	1000.0V	
AC Voltage	200.00mV /2.0000V/20.000V/200.00V	±(0.8%+10dig)
	750V	±(1.0%+10dig)
DC Current	200.00mA	±(0.8%+10dig)
	10.000A	±(2.5%+10dig)
AC Current	200.00mA	±(1.0%+10dig)
	10.000A	±(2.8%+10dig)
Resistance (Ω)	200.00Ω/2.0000kΩ/20.000kΩ/200.00kΩ/2.0000MΩ	±(0.8%+10dig)
	20.000MΩ	±(1.0%+3dig)
	100.00MΩ	±(5.0%+10dig)

Capacitance (F) ^[1]	20.000nF/200.00nF/2.0000uF/20.000uF/200.00uF/2.0000mF	±(3.0%+10dig)
Frequency Response (Hz)	(40 - 1000) Hz	

[1] When measuring AC voltage/current or capacitance, accuracy guarantee range is 5% to 100% of the range.

Other

Display	
Display Type	2.8inches color LCD
Resolution	240 × 320 pixels
Color	65536 color, TFT
Environment	
Temperature	Working Temperature:0℃~40℃ Storage Temperature:-20℃~60℃
Relative Humidity	≤90%RH; no condensation
Height	2,000 meters
Cooling	Fan cooling, temperature intelligent speed control
Other	
Communication Port	USB communication, compatible with SCPI communication protocol
USB Charging Port	5V/1A charging
Dimension	82mm (Width) × 142mm (Height) ×226mm (Length)
Weight	Approx. 1.5 kg



7007020100151

V1.0.0