

中景园电子

专业OLED、TFT-LCD模组供应商

APPROVAL SHEET

承 认 书

记录编号： 版本：v0.0

Customer 客户名称	
Part NO. 产品型号	ZJY144SN005
Product type 产品内容	Mode: Transmissive type .Normally white. TFT LCD Module LCD Module: Graphic 128RGB*128Dot-matrix
Remarks 备注栏	☐ APPROVAL FOR SEPCIFICATIONS ONLY ☒ APPROVAL FOR SEPCIFICATIONS AND SAMPLE
Signature by Customer: 客户确认签章	

中景园确认

核准	审核	定制

客户确认

核准	审核	审核

中景园电子

专业OLED、TFT-LCD模组供应商

TABLE OF Contents

1. General Description.....	3
2. Features.....	3
3. Mechanical Specification.....	3
4. Mechanical Dimension.....	4
5. Maximum Ratings.....	5
6. Electrical Characteristics.....	5
7. Backlight Characteristic.....	5
8. Module Function Description.....	7
9. Electro-optical Characteristics.....	9
10. Reliability.....	13
11. Inspection Standards.....	14
12. Precautions For Using LCD Modules.....	18
13. Factory.....	19
14. Revision History.....	19

中景园电子

专业OLED、TFT-LCD模组供应商

1.General Description

Z144SN005 is a 128RGB*128 dots matrix TFT LCD module. It has a TFT panel composed of 384sources and 128gates. The LCM can be easily accessed by micro-controller.

2. Features

Display Mode	Transmissive
	a-TFT
Display Format	Graphic 128RGB*128 Dot-matrix
Input Data	SPI interface
Viewing Direction	12 o'clock
Drive	ST7735S


3. Mechanical Specification

Item	Specifications	Unit
Dimensional outline	29.50(W)*36.50(H)*2.25+/-0.1(T) (FPC not include)	mm
Resolution	128RGB*128	dots
LCD Active area	25.50 (W)*26.50 (H)	mm
Pixel size	0.20(W)*0.20(H)	mm

4. Mechanical Dimension

中景园电子

专业OLED、TFT-LCD模组供应商



中景园电子

专业OLED、TFT-LCD模组供应商

5. Maximum Ratings

Item	Symbol	Min	Max	Unit	Note
Supply voltage	V	-0.3	4.6	V	
Operating temperature	V _T	-0.3	V _{CC} +0.3	V	
Storage temperature	T _{OPR}	-20	70	°C	
Storage temperature	T _{STR}	-30	80	°C	

6. Electrical Characteristics

Item		Symbol	Condition	Min.	Typ.	Max.	Unit
Supply voltage	Logic	V _{CC}		2.7	2.8	3.3	V
Input Voltage	H level	T _{IH}		0.8*IOVCC		IOVCC	V
	L level	T _{IL}		-0.3		0.2* IOVCC	
Storage temperature		I _{DD}	With internal voltage generation V _{CC} =2.8V; T _{emp} =25°C			TBD	mA

7. Backlight Characteristic

Item	Symbol	Min	Typical	Max	Unit
LED module Forward voltage	V _{LED}	3.0	3.2	3.4	V
LED module current	V _{LED}		20		mA
L/G Surface Luminance ★1	L _S	1800			Cd/m ³
LCM Surface brightness uniform ★2	L _D	80			%

★ 1Test condition is:

(a) Center point on active area.

(b)Best Contrast.

★2Uniform measure condition:


(1)Measure 9 point. Measure location show below;

(2)Uniform=(Min. brightness /Max. brightness)*100%

中景园电子

专业OLED、TFT-LCD模组供应商

(3)Best Contrast.



中景园电子

专业OLED、TFT-LCD模组供应商

8. Module Function Description

8.1 Pin Descriptions

PIN No.	Symbol	Description	Notes
1	NC	No connection (悬空)	
2	GND	Ground (接地脚)	
3	LED-	Cathode of Backlight (背光负极供电脚)	
4	LED+	Anode of Backlight (3.0V-3.4V) (背光正极供电脚)	
5	GND	Ground (接地脚)	
6	/RESET	LCM Reset pin (屏复位脚)	
7	A0	Register select pin (指令/数据寄存器选择脚) RS='1': Display data. (RS='1':选择数据寄存器) RS='0': Command data. (RS='0':选择指令寄存器)	
8	SDA	Serial data input / output. (串口数据线)	
9	SCK	Serial clock pin. (串口时钟线)	
10	VCC	Power supply for Analog (2.8V-3.3V) (系统电压)	
11	IOVCC	Power supply for interface(1.8V-3.3V) (I/O 口电压)	
12	CS	Chip select pin ("Low" enable) (屏驱动芯片片选脚, 低电平有效)	
13	GND	Ground (接地脚)	
14	NC	No connection (悬空)	

NOTE: 1. IOVCC Connected to VCC(应用时可以把 IOVCC 和 VCC 连在一起供 2.8-3.3V 的电压。
2.背光 LED 可以单独供电, 也可以和 VCC 共用一组电压供电。

中景园电子

专业OLED、TFT-LCD模组供应商

8.2 Timing characteristics.

Serial Interface Characteristics (4-line Serial)




Figure 7 4-line Serial Interface Timing

中景园电子

专业OLED、TFT-LCD模组供应商

Ta=25 °C, VDDI=1.65~3.7V, VDD=2.5~4.8V

Signal	Symbol	Parameter	MIN	MAX	Unit	Description
CSX	TCSS	Chip Select Setup Time (Write)	45		ns	
	TCSH	Chip Select Hold Time (Write)	45		ns	
	TCSS	Chip Select Setup Time (Read)	60		ns	
	TSCC	Chip Select Hold Time (Read)	65		ns	
	TCHW	Chip Select "H" Pulse Width	40		ns	
SCL	TSCYCW	Serial Clock Cycle (Write)	66		ns	-Write Command & Data Ram
	TSHW	SCL "H" Pulse Width (Write)	15		ns	
	TSLW	SCL "L" Pulse Width (Write)	15		ns	
	TSCYCR	Serial Clock Cycle (Read)	150		ns	-Read Command & Data Ram
	TSHR	SCL "H" Pulse Width (Read)	60		ns	
	TSLR	SCL "L" Pulse Width (Read)	60		ns	
D/CX	TDCS	D/CX Setup Time	10		ns	
	TDCH	D/CX Hold Time	10		ns	
SDA (DIN) (DOUT)	TSDS	Data Setup Time	10		ns	For Maximum CL=30pF For Minimum CL=8pF
	TSDH	Data Hold Time	10		ns	
	TACC	Access Time	10	50	ns	
	TOH	Output Disable Time	15	50	ns	

Table 7 4-line Serial Interface Characteristics

9.Electro-optical Characteristics


Item	Symbol	Conditions	Temp	Min.	Typ.	Max.	Unit	Note
Response Time	T _R	$\theta = \phi = 0$	25°C		TBD	TBD	msec	NOTE2
	T _F				TBD	TBD		
Viewing Angle Range	$\phi = 0^{\circ} (6'')$	$\phi = 90^{\circ} (3'')$	$\phi = 180^{\circ} (12'')$			$\phi = 270^{\circ} (9'')$		NOTE3
$\theta (25^{\circ}\text{C}) \text{ CR} \geq 10$	TBD	TBD	TBD			TBD		NOTE3

The above "viewing angle" is the measuring position with the largest contrast ratio. Not for good image quality. Viewing direction for good image quality is 12 O'clock.


中景园电子

专业OLED、TFT-LCD模组供应商

- For panel only
- Electro-Optical Characteristics Test Method




$$V_{op} = (V_{10, ON} + V_{90, OFF})/2$$



.Note2.Definition of Optical Response Time:

中景园电子


专业OLED、TFT-LCD模组供应商



.Note3.Definition of Viewing Angle θ and ϕ :

中景园电子

专业OLED、TFT-LCD模组供应商




Note4.Definition of Contrast ratio (CR):

中景园电子

专业OLED、TFT-LCD模组供应商

$$CR = \frac{\text{Brightness of Non-selected Segment (B2)}}{\text{Brightness of Selected Segment (B1)}}$$



10. Reliability

10.1Mtbf

The LCD module shall be designed to meet a minimum MTBF value of 50000 hours with normal

10.2Test condition

NO.	ITEM	CONDITION	CRITERION
1	High Temperature Non-Operating Test	80℃*240Hrs	。 No Defect Of Operational Function In Room Temperature Are Allowable
2	Low Temperature Non-Operating Test	-30℃*240Hrs	
3	High Temperature/Humidity Non Operating Test	60℃*90%RH*240Hrs	
4	High Temperature Operating Test	70℃*240Hrs	。 IDD of LCM in Pre-and Post-Test Should Follow Specification
5	Low Temperature Operating Test	-20℃*240Hrs	
6	Thermal Shock Test	-20℃ (30Min) ↔70℃ (30Min) *10CYCLES	

Notes:

1. Judgments should be made after exposure in room temperature for two hours.
2. The distill water is used for the high temperature/humidity test.
3. The sample above is individually for every reliability tests condition.

中景园电子

专业OLED、TFT-LCD模组供应商

11.Inspection standards

1.AQL(Acceptable Quality Level)


AQL of major and minor defect.

	MAJOR DEFECT	MINOR DEFECT
AQL	0.65	1.5

2. Basic conditions for inspection

The LCM face to us, in normal environment, the lux is 1000 ± 200 . (Darkroom's lux: 100 ± 50), About an angle of incidence 30, a distance of 30 cm with an angle of 45 degree to check the products without uncovering the film!

(As shown below)



3.Inspection item and criteria




3.1 Visual inspection criterion in immobility

3.1.1Glass defect


NO	Defect item	Criteria	Remark
1	Dimension Unconformity (Major defect)	By Engineering Drawing	
2	Cracks (Major defect)	1. Linear cracks panel 2. Nonlinear crack contrast by limited sample 【Reject】	
3	Glass extrude the conductive area (minor defect)	a: disregards and no influence assemblage. 1) $b \leq 1/3$ Pin width (non bonding)	A: Length, b: Width

中景园电子

专业OLED、TFT-LCD模组供应商


		area) 2)bonding area $\leq 0.5\text{mm}$ 【Accept】	
4	Pin-side ,conductive area damaged (minor defect)	(a c: disregards) $b \leq 1/3$ of effective length for bonding electrode 【Accept】	a: length, b: Width, c: Thickness 
5	Pin-side,non-conductive area damaged (minor defect)	1)Damage area don't touch the ITO (Including contraposition mark, except scribing mark) 【Accept】 2) $C < T$ $b \leq BM1/3$ of width 【Accept】 3) $c = T$ b not touch the seal glue 【Accept】 4)a disregards	a: Length, b: Width c: Thickness 
6	Non-pin-side damage (minor defect)	$c < T$ 1)b exceeds $1/3BM$ 【Reject】 $c = T$ b not touch the seal glue 【Reject】	c: Thickness b: width of  damage

3.1.2LCD appearance defect(View area)


NO	Defect item	Criteria		Remark
1	Fiber、 glass cratch、 polarizer scratch/folded (minor defect)	Specification	Allowable	note1:L: Length, W: Width note2: disregard if out of AA 
		$W \leq 0.03\text{mm}$	disregard	
		$0.03\text{mm} < W \leq 0.05\text{mm};$ $L \leq 3.0\text{mm}$	2	
		$0.05\text{mm} < W \leq 0.1\text{mm};$ $L \leq 3.0\text{mm}$	1	
		$W > 0.1\text{mm}; L > 3.0\text{mm}$	0	

中景园电子


专业OLED、TFT-LCD模组供应商

2	Polarizer bubble、 concave and convex (minor defect)	$\phi \leq 0.2\text{mm}$	disregard	note1: $\phi = (L+W)/2$, L:Length, W :Width note2:disregard if out of AA
		$0.2\text{mm} < \phi \leq 0.3\text{mm}$	2	
		$0.3\text{mm} < \phi \leq 0.5\text{mm}$	1	
		$0.5\text{mm} < \phi$	0	
3	Black dots、dirty dots、 impurities、eye winker (minor defect)	$\phi \leq 0.15\text{mm}$	disregard	note2:disregard if out of AA 
		$0.15\text{mm} < \phi \leq 0.25\text{mm}$	2	
		$0.25\text{mm} < \phi \leq 0.3\text{mm}$	1	
		$0.3\text{mm} < \phi$	0	
4	Polarizer prick (minor defect)	$\phi \leq 0.1\text{mm}$	disregard	note1: $\phi = (L+W)/2$, L=Length, W=Width note2:the distance between two dots>5mm
		$0.1\text{mm} < \phi \leq 0.25\text{mm}$	3	
		$\phi > 0.25\text{mm}$	0	

3.1.3FPC

NO	Defect item	Criteria		Remark
1	Copper screen peel (minor defect)	Copper screen peel 【Reject】		
2	No release tape or peel	No release tape or peel 【Reject】		
3	Dirty dot and impurity of FPC for customer using side (minor defect)	Specification	Allowable	Note1: Cannot have stride ITO impurities
		$\phi \leq 0.25\text{mm}$	2	
		$\phi > 0.25$	0	

3.1.4Black tape & Mara tape


NO	Defect item	Criteria	Remark
1	FPC or H/S black tape (minor defect)	1. shift spec: 1) glue to the polarize 【Reject】 2) IC bare 【Reject】 2. left-and-right spec: 1) exceed of FPC edge or H-S edge 【Reject】 2) IC bare 【Reject】	

中景园电子

专业OLED、TFT-LCD模组供应商

2	No black tape (major defect)	No black tape 【Reject】	
3	Tape position mistake (minor defect)	Not by engineering drawing	
4	Mara tape defect (minor defect)	Peel before pulling the protecting film 【Reject】	

3.1.5 Silicon and Taffy glue



NO	Defect item	Criteria	Remark
1	Quantity of silicon (major defect)	Uncover the ITO and circuit area 【Reject】	note: compared by engineering
2	Taffy glue (major defect)	1.Uncover the reveal copper area【Reject】 2.Cover layer 0.3mm(Min)~3.0mm(Max) 【Reject】	note: if customer has special requirement, refer to the technical document 
3	Depth of glue covering (major defect)	Depth of glue covering overtop front Polarizer 【Reject】	Except of the special requirement

3.2Electrical criteria

NO	Defect item	Criteria	Remark
1	No display (major defect)	No display 【Reject】	
2	Missing line (major defect)	Missing line 【Reject】	
3	Seg-com light and dark (major defect)	Seg-com light and dark 【Reject】	ND filter 2% test
4	No display in immobility (major defect)	No display in immobility 【Reject】	
5	Flicker of Pattern (major defect)	Flicker of Pattern 【Reject】	
6	Mura (major defect)	ND filter 2%test	
7	Over current	Over current	

中景园电子

专业OLED、TFT-LCD模组供应商

	(major defect)	【Reject】		
8	Voltage out of specification (major defect)	Voltage out of specification 【Reject】		
9	Pattern blur, error code (major defect)	Pattern blur, error code 【Reject】		
10	Dark light, Flicker (major defect)	Dark light, Flicker 【Reject】		
11	Black/white dots 、 Dirty dots、 eye winker (major defect)	Specification	Allowable	Note1:disregard if out of AA 
		$\phi \leq 0.15\text{mm}$	disregard	
		$0.15\text{mm} < \phi \leq 0.25\text{mm}$	2	
		$0.25\text{mm} < \phi \leq 0.3\text{mm}$	1	
		$0.3\text{mm} < \phi$	0	
12	Fiber、glass crutch、Polarizer scratch/folded (major defect)	$W \leq 0.03\text{mm}$	disregard	Note1:L: Length, W: Width Note2: disregard if out of AA 
		$0.03\text{mm} < W \leq 0.05\text{mm}$ $L \leq 3.0\text{mm}$	2	
		$0.05\text{mm} < W \leq 0.1\text{mm}$ $L \leq 3.0\text{mm}$	1	
		$W > 0.1\text{mm}; L > 3.0\text{mm}$	0	

12.Precautions for using LCD modules.

12.1 Safety

- (1)Do not swallow any liquid crystal ,even if there is no proof that liquid crystal is poisonous.
- (2)If the LCD panel breaks, be careful not to get liquid crystal to touch your skin.
- (3)If skin is exposed to liquid crystal, wash the area thoroughly with alcohol or soap.

12.2Storage Conditions

- (4)Store the panel or module in a dark place where the temperature is $23 \pm 5^{\circ}\text{C}$ and the humidity is below $45 \pm 20\% \text{RH}$.
- (5)Store in anti-static electricity container.
- (6)Store in clean environment, free from dust, active gas, and solvent.

中景园电子

专业OLED、TFT-LCD模组供应商

(7)Do not place the module near organics solvents or corrosive gases.

(8))Do not crush, shake, or jolt the module.

12.3Handling Precautions

(9)Avoid static electricity, which can damage the CMOS LSI.

(10)The polarizing plate of the display is very fragile, please handle if very carefully.

(11)Do not give external shock.

(12)DO not apply excessive force on the surface.

(13)Do not wipe the polarizing plate with a dry cloth, as it may easily scratch the surface of plate.

(14)Do not use ketonics solvent & Aromatic solvent, use with a soft cloth soaked with a cleaning naphtha solvent.

(15)Do not operate it above the absolute maximum rating.

(16)Do not remove the panel or frame from the module.

12.4Warranty

The period is within twelve months since the date of shipping out under normal using and storage conditions.

13.Factory

FACTORY NAME:

FACTORY ADDRESS:

FACTORY PHONE:

14.Revision history

Version	Revise record	Date
v0.0	Original version	2014-06-16